

STREET BOB 107 FXBB



TYRE PRESSURES. FRONT 36 PSI (All Softails Except FLXR 30 PSI)

REAR 40 PSI (All Softails Except FLFB/S, FXBR/S, FXDRS 42PSI)

LUBRICATION. Check Engine & Transmission Levels on Side Stand.

Primary with machine upright & level.

Engine oil. H-D 360 SAE 20 W 50. 3.8 L. (4Qt)

COLD CHECK. Do not fill above midway.

HOT CHECK. Between “ADD QT” & “FULL HOT”.

Oil Filter $\frac{1}{2}$ - $\frac{3}{4}$ turn from gasket contact.

Transmission & Primary Chaincase oil.

Formula+ Transmission & Chaincase Lubricant.

Transmission 0.83 L. (28 fl oz) Screw in dipstick to check.

Transmission Dipstick - 2.8–8.5 N·m (25–75 in-lbs)

Chaincase 1.06 L. Fill to bottom of Clutch Pressure Plate with machine Level. Approx Dry Fill 1.18L (40 Fl Oz) Wet Fill 1.06L (36 Fl Oz)

All Drain Plugs Torque 14-21 ft-lbs, (19-28.5) Nm.

Clutch Cover Screws 25-35 in lbs (2.8-3.9) Nm